U.S. Department of Transportation
Federal Highway Administration
Federal Lands Highway Office

Worksheet for Determining Moisture/Density Relationships AASHTO T 99 AND AASHTO T 180

Project: _____ Source: _____

Where sampled: _____ Quantity represented: _____

Sample of: _____ Lot No. _____ Sample No. _____

Sampled by: _____ Date: _____ Tested by: _____ Date: _____

AASHTO T 99 ☐ AASHTO T 180 ☐ Method ☐ A ☐ B ☐ C ☐ D

Density Determination								
	Test No. →							
	(a) Wet soil + mold tare [kg]							
	(b) Mold tare [kg]							
	(c) [a-b] Wet wt. [kg]							
	(d) Wet density (*)c [kg/m³]							
	Dry density $(\frac{c}{1 + 0.01w})$ [kg/m³]							

* For molds within tolerance, use a constant factor 1059.43 for methods A and C or 470.74 for methods B and D.

Moisture Determination								
	Pan No. →							
	(r) Wet soil wt. + tare [g]							
	(s) Dry soil wt. + tare [g]							
	(t) Tare [g]							
	(u) Dry soil wt. [s-t] [g]							
	(v) Water wt. [r-s] [g]							
	(w) Moisture $(\frac{v}{u}(100))$ [%]							



Maximum Dry Density:

_____ kg/m³

Optimum Moisture:

_____ %

Save Data Only | Clear Form | Save Form & Data | Email Form | Retrieve Data